



Replacement Axle Guide (2006 and newer VersaMax RT ramp and tilt trailers) ***for Versa Max and Pro 100 Snow Trailers***



Replacement Axle Guide for Versa Max and Pro 100 Snow Trailers



2006 and newer Versa Max RT ramp and tilt trailers

Important: 8" and 10" wheels no longer fit on the current Auto Flex Knott axles. The trailing arm does not have a dog leg like the original axle. Replacing the axle on a trailer with 8" or 10" wheels will require spacer blocks and 13" wheels.

(Tire ST175/80 R13, Load Range D, Bolt Circle 5 on 4 ½)

1. Choose axle accordingly

- 10', 12', 14', and 16' idler axle (no brake)
3000# idler axle, 3.5" rise, 10 degree down
P/N 550-07283-00
- 12', 14', and 16' electric brake axle
3000# electric brake axle, 3.5" rise, 10 degree down
P/N 550-07294-00
- 20', 22', and 28' electric brake trailers
3000# electric brake axle, 1" rise, 10 degree down
P/N 550-07285-00
- 12' Enclosure
3000# idler axle (no brake)
P/N 550-07283-00

2. Axle Mounting Kit

P/N 551-27510-00

*One kit per axle

3. Spacer block (if needed)

Going from 8" or 10" wheels to 13" wheels require 2" spacer block

P/N 551-28700-00 (sold in pair)